

TECHNICAL DATA SHEET

0893 816 001

Container size: 200 ml

HT brake protection

Lubricating, separating and anti-corrosive paste extremely resistant to high temperatures and high pressures.

Fields of application:

For parts on vehicle brake systems, assembly aids on machines, for the prevention of insertion damage and wear on bearings, sliding points and screw and plug connections.

Properties:

- Metal-free recipe does not hinder brake system sensors
- Permanent and high level of lubrication thanks to ceramic components
- Resistant to acids, bases, spray water and salt water
- High-pressure resistant, silicone and AOX-free

Note:

Do not apply to brake discs and brake friction lining!
Shake can well before use!

Technical data:

Chemical basis	Metal-free solid lubricant in synthetic oil with additives
Consistency	Pasty
Colour	Light grey
Temperature range	-40°C to +1400°C
Processing temperature	0°C to +40°C
Density (g/ml at +20°C)	1.32 (± 0.01)
Salt spray test (DIN 50021)	240 h
Water-soluble	No
Shelf life	12 months

TECHNICAL DATA SHEET

Silicone-free	Yes
AOX-free	Yes
Resistant to:	
Spray water	Yes
Salt water	Yes
Acids	Yes
Lyes	Yes

We provide this advice based on our own tests and experience and to the best of our knowledge. We assume no liability for the application results in individual cases, however, due to the large number of applications and the storage and application conditions that lie outside the scope of our influence.

This also applies to the use of the non-binding technical and commercial customer services provided by us. We always recommend that you conduct your own tests. We guarantee the consistent quality of our products. We reserve the right to make technical changes and to further develop our products.